

# Baldor Industrial Portable Generators

Powerchief Model <sup>①</sup>	PC11R	PC17Ri*	PC30H	PC32Ri*	PC40H	PC43Ri*	PC50H	PC60H or PC60HE	PC90VE
<b>List Price</b>	1004	1654	1279	2903	1660	3719	1871	2075/2599	2806
<b>Features</b>									
Switchless Full Pow'R					inc		inc	inc	inc
DC Circuit Breakers	inc	inc		inc		inc			
AC Circuit Breakers	inc	inc	inc	inc	inc	inc	inc	inc	inc
Low Oil Shutdown	inc	inc	inc	inc	inc	inc	inc	inc	inc
Spark Arrestor Muffler	inc	inc	inc	inc	inc	inc	inc	inc	inc
Extended Run Fuel Tank				inc	inc	inc	inc	inc	inc
Tubular Roll Cage			inc		inc		inc	inc	inc
Neoprene Isolators	inc	inc	inc	inc	inc	inc	inc	inc	inc
Focal Vibration System (FVS)					inc		inc	inc	inc
3-Year Warranty <sup>②</sup>	inc	inc	inc	inc	inc	inc	inc	inc	inc
<b>Engine Model</b>									
	Robin/ Subaru	Robin/ Subaru	Honda	Robin/ Subaru	Honda	Robin/ Subaru	Honda	Honda	Vanguard
Horsepower	2.4	2.4	5.5	7	8	9	9	11	16
Cylinder (S)	1	1	1	1	1	1	1	1	2
Displacement-CC	85.8	85.8	163	211	242	265	270	337	480
Starting Systems	Recoil	Recoil	Recoil	Electric/ Recoil	Recoil	Electric/ Recoil	Recoil	Recoil or 12 Volt with Recoil	12 Volt with Recoil
<b>Rating</b>									
Max Rating	1100W	1650W	3000W	3200W	4000W	4300W	5000W	6000W	9000W
Rated	900W	1400W	2500W	2800W	3500W	3800W	4000W	5000W	8000W
Volts	120VAC/ 12VDC	120VAC/ 12VDC	120VAC	120VAC 12 VDC	120/240VAC	120VAC 12VDC	120/240VAC	120/240VAC	120/240VAC
Amps	9.1	13.7	20.8	23.3	29.2/14.6	31.7	33.3/16.7	41.6/20.8	66.7/33.4
db (A) @ 7 meters	59	59	69.9	58	73.5	62	73.3	72	76.1
<b>Receptacles</b>									
Straight (515R) 120V			3-20 Amp						
Straight (520R GFCI) 120V	2-20 Amp	2-20 Amp		2-20 Amp	2-20 Amp	2-20 Amp	2-20 Amp	2-20 Amp	2-20 Amp
Twist Lock (L530R) 120V				1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
Twist Lock (L1430R) 120/240V					1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp
<b>Fuel System</b>									
Fuel Capacity (U.S. Gallons)	4.2 qt	4.2 qt	3.8 qt	3.7 gal	4.6 gal	4.2 gal	4.6 gal	4.6 gal	4.6 gal
Operational Run Time on 1 tankful	4.3 hr	3.5 hr	1.5-2.3 hr	8.4 hr	4-7 hr	6.6 hr	6-10 hr	4-7 hr	3.2-5.6 hr
<b>Dimensions</b>									
Length	19.3"	19.3"	22"	21"	28"	22.8"	28"	28"	28"
Width	11.6"	11.6"	15.75"	18.9"	20.5"	20.7"	20.5"	20.5"	21.50"
Height	17.5"	17.5"	16.5"	22.9"	22.25"	24.3"	22.25"	22.25"	21.0"
Weight	55 lbs	45 lbs	94 lbs	130 lbs	162 lbs	163 lbs	162 lbs	187/193 lbs	217 lbs

**NOTES:** \* PC17Ri, PC32Ri and PC43Ri – Inverter generator – will run the engine at a slower speed for low-power needs and automatically increase speed as more electrical power is required.

• Equipped with Extended Run Fuel Tanks

① Batteries are not included on any Electric Start Models.

② Proper engine maintenance is required. Engine warranty per manufacturer.

**WARNING:** Do not connect generator to any building's electrical system unless a disconnect switch has been installed. Follow local and national electrical codes for proper installation.